

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/022960 A1

- (51) International Patent Classification⁷: **F02F 1/16**,
F16J 10/04, F02B 77/11, F02F 1/18
- (21) International Application Number:
PCT/GB2003/003730
- (22) International Filing Date: 29 August 2003 (29.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0220685.2 5 September 2002 (05.09.2002) GB
- (71) Applicant (for all designated States except US): **INNOGY PLC** [GB/GB]; Windmill Hill Business Park, Whitehill Way, Swindon, Wiltshire SN5 6PB (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **CONEY, Michael**, Willoughby, Essex [GB/GB]; The Pinnocks, Broad Town,


Swindon, Wiltshire SN4 7RG (GB). **CROSS, Andrew**, Mark [GB/GB]; 3 Elm Farm Cose, Upper Minety, Malmesbury, Wiltshire SN16 9PR (GB). **SAMMUT, Richard**, Mark [GB/GB]; 18 Manor Gardens, Hurstpierpoint, Sussex BN6 9UG (GB). **BAKER, Andrew, Robert** [GB/GB]; Redwood House, Albert Road South, Malvern, Worcestershire WR14 3AH (GB).

(74) Agents: **DRAPER, Martyn, John** et al.; Boulton Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: A CYLINDER FOR AN INTERNAL COMBUSTION ENGINE



(57) Abstract: A cylinder for an internal combustion engine. A metallic ring (6) surrounds the top of the cylinder. An insulating ring (7) is provided at the top of the cylinder between the metallic ring and cylinder wall. The axial extent of the insulating ring (7) is less than that of the metallic ring (6) and is determined so that it diverts some of the heat away from the relatively poorly cooled zone towards the top of the cylinder, but does not significantly obstruct the heat flow to surrounding cooling channels (5).

WO 2004/022960 A1